

LINEAR ACTUATOR

XLT SERIES

TOUGH
IP66 RATED

COMPETITIVE
ECONOMICAL

SIMPLE
PLUG AND PLAY



Duff-Norton's NEW XLT Series linear actuator is the ideal choice for applications requiring **durability and long life**. Designed for harsh working conditions, the XLT Series is suitable for **heavy-duty applications** including machinery, industrial equipment and off road vehicles. The XLT Series is **IP66-rated** for enhanced protection against dust and moisture.



 **Duff-Norton**[®]

XLT SERIES SPECIFICATIONS

Part Number	Rated Load		Stroke Length		Retracted Length		Voltage	Current Draw at Rated Load	Lifting Speed at Rated Load		Limit switch	Duty Cycle at Rated Load
	lbs	N	in	mm	in	mm	VDC	amp	in/s	mm/s		
ACME SCREW MODELS												
192025394	340	1512	1.97	50	8.27	210	12	15.4	1.06	27	Yes	20%
192025406							24	7.7				
192025395			3.94	100	10.24	260	12	15.4				
192025407							24	7.7				
192025396			5.91	150	12.21	310	12	15.4				
192025408							24	7.7				
192025397			7.87	200	14.17	360	12	15.4				
192025409							24	7.7				
192025398			9.84	250	16.14	410	12	15.4				
192025410							24	7.7				
192025399	11.81	300	18.11	460	12	15.4						
192025411					24	7.7						
192025400	565	2513	1.97	50	8.27	210	12	14.0	0.56	14	Yes	20%
192025412							24	7.0				
192025401			3.94	100	10.24	260	12	14.0				
192025413							24	7.0				
192025402			5.91	150	12.21	310	12	14.0				
192025414							24	7.0				
192025403			7.87	200	14.17	360	12	14.0				
192025415							24	7.0				
192025404			9.84	250	16.14	410	12	14.0				
192025416							24	7.0				
192025405	11.81	300	18.11	460	12	14.0						
192025417					24	7.0						
BALL SCREW MODELS												
192025418	565	2513	1.97	50	8.27	210	12	25.0	1.89	48	Yes	20%
192025436							24	12.5				
192025419			3.94	100	10.24	260	12	25.0				
192025437							24	12.5				
192025420			5.91	150	12.21	310	12	25.0				
192025438							24	12.5				
192025421			7.87	200	14.17	360	12	25.0				
192025439							24	12.5				
192025422			9.84	250	16.14	410	12	25.0				
192025440							24	12.5				
192025423	11.81	300	18.11	460	12	25.0						
192025441					24	12.5						
192025424	790	3514	1.97	50	8.27	210	12	18.0	1.00	25	Yes	20%
192025442							24	9.0				
192025425			3.94	100	10.24	260	12	18.0				
192025443							24	9.0				
192025426			5.91	150	12.21	310	12	18.0				
192025444							24	9.0				
192025427			7.87	200	14.17	360	12	18.0				
192025445							24	9.0				
192025428			9.84	250	16.14	410	12	18.0				
192025446							24	9.0				
192025429	11.81	300	18.11	460	12	18.0						
192025447					24	9.0						
192025430	1015	4515	1.97	50	8.27	210	12	13.0	0.55	14	Yes	20%
192025448							24	6.5				
192025431			3.94	100	10.24	260	12	13.0				
192025449							24	6.5				
192025432			5.91	150	12.21	310	12	13.0				
192025450							24	6.5				
192025433			7.87	200	14.17	360	12	13.0				
192025451							24	6.5				
192025434			9.84	250	16.14	410	12	13.0				
192025452							24	6.5				
192025435	11.81	300	18.11	460	12	13.0						
192025453					24	6.5						



Contact factory for potentiometer models



北京泰瑞恩商贸有限公司
Beijing Torion Trading Co., Ltd.

Tel: 13801253818 Fax: 010-84067150
www.torion.cn sales@torion.cn

